


# Antidote

## Urethane Fortified Floor Finish



**Directions For Use:**  
**IMPORTANT! READ THE LABEL FIRST!**

**Antidote is a hard floor surface finish. Can be used on terazzo, concrete, marble, ceramic tile, and vinyl. DO NOT dilute.**

**Apply minimum of 2-3 coats using a clean finish mop or applicator. To reach desired gloss and protection, apply additional coats as necessary. Allow floor to dry thoroughly between coats.**

**Antidote can be easily removed with **Bonesaw** floor stripper.**

**Maintain with **Therapy** neutral cleaner or **Booster Shot** maintainer. For best results, buff with light hair pad, also available through **FloorCareMD**.**

**Prevent eye and skin contact. Wear safety goggles & rubber gloves when handling. Keep off clothing. Wash thoroughly after handling.**

**FloorCareMD** **1-800-344-7572**  
**www.FloorCareMD.com**

### First Aid

**For eye contact:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing.

**For contact with skin or clothing:** Immediately flush skin with plenty of water while removing contaminated clothing or footwear. See a physician for further treatment advice. Wash clothing thoroughly before reuse.

**For inhalation:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial resuscitation, preferably mouth to mouth. Call a doctor for further treatment advice.

**For Ingestion:** DO NOT induce vomiting. Drink one cup of water as soon as possible to rinse throat. Immediately call poison control or doctor for treatment advice. DO NOT give anything by mouth if unconscious.

**24 HOUR EMERGENCY PHONE**  
**1-800-535-5053 or 352-323-3500**

Material Safety Data Sheet (MSDS) and emergency medical information. Contact local poison control center or doctor. Keep this product label with you.

### NOTE TO PHYSICIAN:

This product has a low odor toxicity similar to latex paint.

1- Health	0= minimal risk
0- Flammibility	1= slight risk
0- Reactivity	2= moderate risk
	3= serious risk
	4= extreme risk

**WARNING: CAUSES EYE IRRITATION**

**KEEP OUT OF REACH OF CHILDREN**

Contents below:	CAS Number
Water	7732-18-5
Acrylate Polymer	6218-77-2
Polyethylene	668441-17-8
Diethylene glycol ether	111-90-0
Tributoxyethyl phosphate	78-51-3